

# Elite Flow Series A2L/A3



## KEY FEATURES

- Spark proof, double stage, dual voltage vacuum pumps
- High performance A2L range
- Sparkproof switches
- Hard wired 16.4ft (5m) lead
- Dual voltage
- Solenoid valve
- Easy access oil drain
- 2 year warranty

Description	Elite Flow 1.5 A2L/A3	Elite Flow 5 A2L/A3	Elite Flow 9 A2L/A3
Model / Part No.	<b>TEP-310-A2L</b>	<b>TEP-141-A2L</b>	<b>TEP-231-A2L</b>
Suitability	All All standard A2L and A3 applications		

## Specification

Stage	Double		
CFM	40 / 1.4	151 / 5.3	251 / 8.9
Ultimate vacuum (microns)	15		
Free air displacement (CFM, l/m)	1.4 / 40	5.3 / 151	8.9 / 251
Power supply	115-230V, 60Hz		
Motor size HP	1/4	1/2	2/3
Power cord connection to pump	IEC		
Oil capacity	4.7 fl.oz. (140 ml)	18.2 fl.oz. (540 ml)	20.9 fl.oz. (620 ml)
Intake fittings	1/4 SAE, 3/8 SAE and 1/2 ACME		
Weight	9.9 lb (4.5 kg)	24.2 lb (11 kg)	32.6 lb (14.8 kg)
Dimensions	10 x 4 1/8" x 8 3/4" (265 x 105 x 220 mm)	14" x 5 1/2" x 11" (348 x 140 x 272 mm)	15" x 6 1/4" x 11 1/4" (380 x 160 x 285 mm)