

Velo-X Twin Recovery Unit



KEY FEATURES

- High recovery rates
- Lightweight
- R32 / R1234YF / HFC / HCFC / CFC / HFO / A2L / A3
- Oil free compressor
- 16.4ft (5m) hard wired cable & spark-proof switch
- 2 year warranty

Part No.	TER-100-A2L
Suitability	All standard A2L and A3 applications
Specification	
Power Supply	Universal Voltage 100-240VAC 50/60Hz
Motor Power	1.25 HP
Motor Type	Variable Speed Brushless DC, 1500-3000 RPM
Maximum Current	12.0 amps
Compressor Type	2 Cylinder Oil-less Reciprocating, Air Cooled
High Pressure Cutout (Manual Reset)	550 PSIG
Operating Temperature Range	32°F (0°C) to 120°F (49°C).
Dimensions	14 1/2" x 9 1/2" x 13" (370mm x 245mm x 325mm)
Weight	24.5 lbs

Refrigerant	Direct Vapor	Final Recovery Vacuum Level	Direct Liquid	Push-Pull Liquid	High Temp. Vapor Rate
R22	0.71 lb/min	10 inHg	9.03 lb/min	12.39 lb/min	0.71 lb/min
	0.32 Kg/min	33.9 KPa	4.10 Kg/min	5.58 Kg/min	0.32 Kg/min
R134a	0.57 lb/min	10 inHg	6.61 lb/min	9.66 lb/min	
	0.26 Kg/min	33.9 KPa	3.00 Kg/min	4.38 Kg/min	
R410a	0.71 lb/min	10 inHg	9.70 lb/min	14.02 lb/min	
	0.32 Kg/min	33.9 KPa	4.40 Kg/min	6.36 Kg/min	

